



## Soldering valves with rotalock connection

### Soldering Valves With Rotalock Connection



- Note:
- 1.The maximum working air pressure:4.5Mpa, hydraulic pressure:6.8Mpa;
  - 2.Suitable medium: R22、R502、R407c、R410a、R134a、R404a、R600a etc. refrigerants and other refrigerating oil;
  - 3.Suitable temperature:-40℃~140℃;
  - 4.The valve series are on the CE and UL list:  0036  SA32723

Note:add access port at left or right or center according to customer adopting one of connecting mode.

SPECIFICATION													
Model	Body Quartet" <sup>1/2</sup> mm×mm	Rotalock Connection	ODS		I mm	H mm	J mm	L mm	Q'ty per carton	Gross weight (kg)	Carton dimension (cm)		
			mm	inch									
RV001	SW19	3/4"-16UNF SW22 (Hex)	6	—	8	20	32.5	104	60	13	38×26×17		
RV002			—	1/4"									
RV003			10	—									
RV004			—	3/8"									
RV005			12	—									
RV006			—	1/2"									
RV007	□20	1"-14UNS SW30 (Hex)	6	—	12	22	32.5	104	60	16			
RV008			—	1/4"									
RV009			10	—									
RV010			—	3/8"									
RV011			12	—									
RV012			—	1/2"									
RV013			16	5/8"									
RV014			18	—									
RV015			—	3/4"									
RV016			12	—									
RV017	□22	1-1/4"-12UNF SW36 (Hex)	—	1/2"	13.5	22	34	107	50	16			
RV018			16	5/8"			36	109					
RV019			18	—			39	112					
RV020			—	3/4"			36	142				30	19
RV021			18	—									
RV022			—	3/4"									
RV023	22	7/8"											
RV024	28	—											
RV025	—	1-1/8"											
RV026	□30	1-3/4"-12UN SW50 (Hex)	18	—	19	28	49.5	142	30	18			
RV027			—	3/4"									
RV028			22	7/8"									
RV029			28	—									
RV030			—	1-1/8"									
RV031			28	—									

RV032	□36		—	1-1/8"	27	31	59	185	20	19
RV033			35	1-3/8"			61	187		
RV034			42	—			65	191		
RV035			—	1-5/8"			72.5	201		
RV036	□50	2-1/4"-12UN SW65 (Hex)	35	1-3/8"	38	43	74.5	203	12	
RV037			42	—			76.5	205		
RV038			—	1-5/8"						
RV039			54	2-1/8"						