

CATEGORY / CAT I / A1



OIL SEPERATOR

OS 7/8"

TECHNICAL INFORMATION

Cooler Fluid Type (Refrigerant)	R22,R134a,404A, R407C,R507A
Capacity (Volume)	2,3 Lt.
Operating Pressure (PS)	33 Bar.
Test Pressure (PT)	48 Bar.
Allowable Temperature (TS)	Min.-20°C / Max. 130°C
Packaging Size & Weight	
Drawn By	Tuncay TEKSEN
Approved	Mustafa DEMIRCI
Date	08.04.2013

CONNECTIONS

		QTY
01	Inlet Connection	7/8" ODS / OS 1 Pcs.
02	Outlet Connection	7/8" ODS / OS 1 Pcs.
03	Oil Return	3/8" SAE Flare 1 Pcs.
04	Top Cover	DD11-6222 Steel 3mm 1 Pcs.
05	Stainless Stel Filter	0,22mm Filter 2 Pcs.
06	Stainless Seperator	1mm 304 1 Pcs.
07	Pipe Of Oil Return	Brass Q8x0,9mm 1 Pcs.
08	Float Ball Of Stainless	Q62x1,2mm 1 Pcs.
09	On&Off Bracket Of Float	Brass 1 Pcs.
10	Needle	Stainless 1 Pcs.
11	Pin Of Spring Steel	Spring Stel Q1,9mm 2 Pcs.
12	Stainless Latch	Stainless Stel 304 1 Pcs.
13	Bottom Cover	DD11-6222 Steel 1 Pcs.
14	Bolt & Nut	M8 1 Pcs.
15	Plate Of Mounting	DD11-6222 Steel 1 Pcs.
16	Segman	3 Pcs.
17	Magnet	Q13 1 Pcs.
18	Stainless Stick	Q5 1 Pcs.
19	Pipe & Tube	Q114 - 3,0 mm 1 Pcs.
	Colour	RAL 5000

Raw Material : 10217-/P235 TR1-EN 10204 3.1 TUBE

TOLERANS

DIN ISO 2768-mK	ISO E
0,5 - 6 mm	+ 0,1
6 - 30 mm	+ 0,2
30 - 120 mm	+ 0,3
120 - 400 mm	+ 0,5
400 - 1000 mm	+ 0,8

GVN SOGUTMA
 Uniteleri San. ve Tic. Ltd. Şti.
 www.gvn.com.tr

Tel. : +90 (212) 230 2113 - 232 4147
 Fak. : +90 (212) 231 6395 - 2325296
 Add : Dolapdere Cad. Lalecer Sok.
 No:7, 34375, Pangalti, Istanbul, TURKEY
 E-mail : info@gvensogutma.com

BEST QUALITY. BEST SERVICE. BEST PRICE

MADE IN TURKEY

