

VRP-6DLi



Set	pump, oil
Flow	170 l/min / 6 CFM
Vacuum Level (Partial / Total)	0,2 Pa / 15 microns
Motor power	0,37 kW (0,5 KM)
Compression Stages	2
Power supply	battery 18V
Motor speed 50 Hz	2400 rpm
Noise level	≤65 dB
Inlet connection	1/4", 3/8", 1/2" SAE
Oil capacity	0,417 l
Oil type	mineral, viscosity: 46 mm ² /s
Dimensions	355 x 127 x 255 mm
Weight	9,6 kg
Protection level	IP20
Operating temperature	5 - 40°C
Storage temperature	-10 - 50°C
Minimum oil temperature for startup	5°C
Shut-off valve	yes (manual)
Exhaust plug	in the handle

VRP-6DLi

Vacuum gauge	no
Motor type	DC 18 V
Work time	about 60 min (battery 9 Ah)
Packaging	carton

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

VRP-6DLi

A high-flow, two-stage cordless VALUE vacuum pump designed for working with HFC and HFO refrigerants (e.g., R32, 1234yf).

Main features:

- two-stage
- battery-powered
- high-quality vacuum
- large sight glass for monitoring oil level
- forced oil circulation ensuring tight vane operation and pump cooling
- lightweight and efficient DC motor
- spark-free design, suitable for working with R32 and 1234yf refrigerants
- set: pump, oil
- optional battery adapters available: Bosch, Milwaukee, DeWalt, Makita
- gas ballast valve - prevents moisture from entering the pump oil



VRP-6DLi



VRP-6DLi



VRP-6DLi



VRP-6DLi

