

# 1/4" ALUMINUM 2-VALVE ZEPPELIN®

# ZEPPELIN

## 2-VALVE ALUMINUM MANIFOLD

**MADE IN USA**

**COLOR CODED REFRIGERANT DIALS FOR EASY READING**

**PULL-OUT PROOF HANGING HOOK**

**\$4.00**

The amount the U.S. spends on Chinese imports for every \$1 China spends on U.S. goods (Business Insider 2011).

**SURGE DAMPENED GAUGES FOR REDUCED NEEDLE MOVEMENT**

**ORIGINAL FREE FLOATING DUAL O-RING SEALING SYSTEM FOR FASTER EVACUATION AND CHARGING. SEE PAGE 18 FOR DESCRIPTION**

**AVAILABLE FOR USE WITH R410A**

**AVAILABLE WITH 2-1/2" AND 3-1/8" SIZE GAUGES**

### METRIC INFORMATION

OFFERED WITH 63.5 MM (2-1/2") METRIC GAUGES READING BAR/PSI, KPA/PSI, AND KG/CM<sup>2</sup>. FOR INFORMATION ON METRIC VERSIONS, PLEASE REFER TO PAGE 31.

**ALL METAL GAUGES**

**24225**

**PRECISELY MACHINED ANODIZED ALUMINUM BODY**

**SOFT GRIP RUBBER HAND WHEELS REDUCE TURNING TO OPEN/CLOSE**

**REPLACEABLE INTAKE/HOSE HOLDER FITTINGS FOR STORAGE**

## 2-VALVE ALUMINUM MANIFOLD

The American made aluminum Zeppelin® series of manifolds feature durable molded "Soft Grip" rubber handles with fingertip grooves that ease opening and closing while the improved stem design means "Full Open" in only 2½ turns. The aluminum Zeppelin® series, available in 2-valve and 4-valve, also incorporates cutting edge styling and technology to significantly reduce the weight of the manifold.

In addition, JB also offers an increased selection of gauges in metal cases and refrigerant combinations. Standard 2-1/2", large glow-in-the-dark 3-1/8", and liquid-filled 3-1/8" gauges can be coupled with different refrigerant combinations and JB's multiple hose options to serve any application. All manifolds include a 60" (152.3 cm) hose set unless noted otherwise.

DEEP VACUUM  
CHARGING EQUIPMENT  
GAUGES  
HOSES  
ACCESS VALVES  
TOOLS & ACCESSORIES  
BRASS FITTINGS  
REPAIR PARTS  
INDEX



# METRIC ZEPPELIN® MANIFOLD

## METRIC ALUMINUM ZEPPELIN®

JB's Zeppelin® manifold is offered with 63.5 mm (2-1/2") metric gauges in BAR/PSI, kPA/PSI, and kg/cm<sup>2</sup> as well as Standard CL and Kobra® CLE series hoses. Look to page 22 for all the features of JB's 2-valve aluminum manifold.

Available with 80 mm (3-1/8") metric gauges in select quantities. For more information, please contact sales@jbind.com or 800.323.0811.



Includes (3) 60" hoses (unless noted)	BAR/PSI	kPA/PSI	kg/cm <sup>2</sup>
---------------------------------------	---------	---------	--------------------

R-134A

No hose set	28732	28832	28932
CCLA standard hose with quick couplers	28735	28835	28935

R-22

R-404A

R-410A

No hose set	28752	28852	28952
CCLC Kobra® hose set	28754	28854	28954
CCLBV Kobra® hose set with ball valve	28759	28859	28959

R-12

R-22

R-502

No hose set	28772	28872	28972
CCL standard hose set (36"/91 cm hose)	28770	28870	28970
CCL standard hose set (60"/152 cm hose)	28774	28874	28974
CCLS Kobra® hose with UL R-410A secure seal (60"/152 cm hose)	28776	28876	28976

R-134A

R-404A

R-507

No hose set	28782	28882	28982
CCL standard hose set (36"/91 cm hose)	28780	28880	28980
CCL standard hose set (60"/152 cm hose)	28784	28884	28984
CCLC Kobra® hose (60"/152 cm hose)	28786	28886	28986
CCLS Kobra® hose with UL R-410Asecure seal (60"/152 cm hose)	28788	28888	28988