

Series	Model	Displacement (cc/rev)	CoolingCapacity (W)	CoolingCapacity (Btu/h)	COP (W/W)	Capacitor (µF/V)	Height (mm)	Testing Condition
--------	-------	-----------------------	---------------------	-------------------------	-----------	------------------	-------------	-------------------

T1 R410A Constant-speed T1 R410A
[1φ]220-240V 50Hz

D	ASD042SV	4.2	940	3207	2.65	8/450	217.8	ASHRAE/T
	ASD063SV	6.3	1460	4982	2.72	17/400	238.8	ASHRAE/T
	ASD089SV	8.9	2112	7206	2.85	25/400	248.8	ASHRAE/T
	ASD096TV	9.6	2315	7899	2.83	30/400	248.8	ASHRAE/T
	ASD102XV	10.2	2440	8325	3.00	25/400	248.8	ASHRAE/T
G	ASG102UV	10.2	2450	8359	3.02	30/450	261.0	ASHRAE/T
	ASG108TV	10.8	2510	8564	2.90	25/450	261.0	ASHRAE/T
	ASG125UV	12.5	2930	9997	2.93	30/450	261.0	ASHRAE/T
	ASG135TV	13.5	3250	11089	3.03	30/450	261.0	ASHRAE/T
L	ASL133TV	13.3	3200	10918	3.00	30/450	273.6	ASHRAE/T
	ASL140TV	14.0	3370	11498	3.00	30/450	273.6	ASHRAE/T
	ASL150UV-1	15.0	3555	12130	3.00	35/450	289.0	ASHRAE/T
	ASL160UV	16.0	3780	12897	3.00	35/450	289.0	ASHRAE/T
	ASL180UY	18.0	4350	14842	3.03	35/450	304.0	ASHRAE/T
	ASL190UY	19.0	4590	15661	3.00	45/450	304.0	ASHRAE/T
	ASL211SV-1	21.1	5085	17350	2.90	50/450	289.0	ASHRAE/T
H	ASH184TV-1	18.4	4520	15422	3.10	40/450	301.1	ASHRAE/T
	ASH232SV	23.2	5510	18800	2.90	60/400	298.5	ASHRAE/T
	ASH244UV-1	24.4	5800	19790	3.02	50/450	315.5	ASHRAE/T
	ASH264SV	26.4	6300	21496	2.85	50/450	298.5	ASHRAE/T
	ASH280TV	28.0	6830	23304	3.00	70/450	312.9	ASHRAE/T
TH	ATH290TV	29.0	7130	24328	2.98	45/450	364.0	ASHRAE/T
	ATH290CV	29.0	7125	24311	2.88	60/450	358.0	ASHRAE/T
	ATH307RV	30.7	7330	25010	2.90	50/450	358.0	ASHRAE/T
	ATH325CV	32.5	7780	26545	2.87	60/450	358.0	ASHRAE/T
	ATH356CV	35.6	8440	28797	2.85	65/450	358.0	ASHRAE/T
	ATH420SV	41.8	10100	34461	2.95	90/450	375.8	ASHRAE/T

T1 R410A Constant-speed T1 R410A
[3φ]380V 50Hz

H	ASH286UC	28.6	6830	23304	3.05	--	315.5	ASHRAE/T
TH	ATH280TC	28.0	6750	23031	2.92	-	351.4	ASHRAE/T
	ATH307UC3	30.7	7490	25556	3.08	-	375.8	ASHRAE/T
	ATH356UC	35.6	8680	29616	3.08	--	375.8	ASHRAE/T
	ATH420UC	42.0	10150	34632	3.03	--	375.8	ASHRAE/T

T1 R410A Constant-speed T1 R410A
[1φ]220V 50Hz (Low Voltage)

G	ASG096GV	9.6	2355	8035	2.83	35/450	261.0	ASHRAE/T
	ASG108GV	10.8	2610	8905	2.84	35/450	261.0	ASHRAE/T
	ASG130GV	13.0	3170	10816	2.83	35/450	261.0	ASHRAE/T
L	ASL145GV	14.5	3500	11942	2.82	40/450	289.0	ASHRAE/T
H	ASH179GV	17.9	4250	14501	3.09	40/450	301.1	ASHRAE/T
	ASH210GV	21.0	5230	17845	2.99	55/450	301.1	ASHRAE/T
	ASH232GV	23.2	5740	19585	3.01	60/450	315.5	ASHRAE/T
	ATH290GV	29.0	7060	24089	2.98	60/450	358.0	ASHRAE/T