

Specification_ Constant speed (R410A, 1Piston)

Refrigerant	Type	Frequency	Voltage	Series	Model	Cooling Capacity		Input	EER	COP	Test Condition				
						Btu/hr	Watts	Watts	Btu/W.hr	W/W					
R410A	1piston	50Hz	1 Φ ,220/240V	GJS	GJS134P	10,120	2,966	1,150	8.80	2.58	ASHRAE				
					GJS208P	16,800	4,923	1,645	10.21	2.99	ASHRAE				
					GJS222P	18,800	5,509	1,825	10.30	3.02	ASHRAE				
					GJS230P	19,000	5,568	1,882	10.10	2.96	ASHRAE				
					GP	GP270P	23,100	6,769	2,330	9.91	2.91	ASHRAE			
						GP280P	23,700	6,945	2,370	10.00	2.93	ASHRAE			
				GP290P		24,700	7,238	2,470	10.00	2.93	ASHRAE				
				GPS	GPS250P	21,200	6,212	2,038	10.40	3.05	ASHRAE				
					GPS270P	23,200	6,799	2,210	10.50	3.08	ASHRAE				
					GPS280P	23,800	6,974	2,288	10.40	3.05	ASHRAE				
									GPS290P	24,700	7,238	2,375	10.40	3.05	ASHRAE

Note 1 : Figures in the table are subject to change without prior notice for performance improvement.


Note 2 :

Test condition	Condenser temperature	Evaporation temperature	Suction temperature	Sub cool
ASHRAE	54.4°C	7.2°C	35°C	8.3°C


Dimension							
A	B	C	D	E	F	G	H
171.0	213.0	190.5	113.3	75.0	127.3	8.06	9.7
237.0	298.9	288.2	115.5	75.0	127.3	9.70	12.8
237.0	297.2	320.0	113.0	75.0	127.3	9.70	12.8
237.0	298.8	286.4	115.5	75.0	127.3	9.70	12.8
250.0	325.0	340.1	123.1	75.0	145.4	9.70	75.0
250.0	353.3	403.4	132.5	90.0	145.4	9.70	16.0
250.0	353.3	403.4	132.5	90.0	145.4	9.70	16.0
250.0	328.0	361.3	132.5	90.0	145.4	9.70	16.0
250.0	328.0	345.3	123.4	75.0	145.4	9.70	16.0
250.0	328.0	345.3	123.4	75.0	145.4	9.70	16.0
250.0	353.3	383.4	132.5	90.0	145.4	9.70	16.0

* I : Custom angles are available upon request between 15° and 105°
 * C, D, E, Φ G, Φ H : Dimensions may vary according to customer needs.

GJS



GP



GPS

