




1



GR25C-6ID.BD.CR | 115666/A01 | Portfolio STD-WW | Cpro ECblue

Standard design with ECblue motor and integrated electronics

Material of impeller:

- ZAmid - high performance composite material

Color Coating:

- Color coating in RAL5002 (Ultra marine-blue)

Mains voltage motor size B_:

- 1~ 200...277 V; 50/60 Hz

Mains voltage motor size D_:

- 1~ 200...277 V; 50/60 Hz
- 3~ 200...240 V; 50/60 Hz
- 3~ 380...480 V; 50/60 Hz

Mains voltage motor size G_:

- 3~ 200...240 V; 50/60 Hz
- 3~ 380...480 V; 50/60 Hz

Thermal class:

- THCL155

Thermal protection:

- Protection with active temperature management

Protection:

- IP54

Coating:

- Motor painted in RAL5002 (Ultra marine-blue)

Controller (only motor size B_):

- Activation via external speed setting 0-10 V / PWM, Communication interface on request
- Standard cable length: 60 cm

Controller (only motor size D_, G_):

FANselect



- **BASIC:**

Activation via external speed setting 0-10 V / PWM Art. no. ER- and GR-module
in basic version

- **PREMIUM:**

Integrated control functionality, Communication interface on request

Cable glands:

- Motor size D: 3 x M16 x 1.5
- Motor size G: 3 x M20 x 1.5

Ambient temperature:

- Minimum permissible ambient temperature: -20 °C*
- Maximum permissible ambient temperature: 40 °C or see data sheet

***Continuous operation with occasional starts (S1) according to DIN EN 60034-1: 2011-02. Occasional starting between -35 ° C and -25 ° C is permissible. Permanent operation below -25 ° C only possible with special bearings for refrigeration applications on request.**



fan data

16/12/2021

version FANselect V 1.01 (211209), AMCA V 1.03 September, 2021 / 1.21.12.09 | 53567 | (user ZAFS43567)



type	GR25C-6ID.BD.CR
article no.	115666/A01 Portfolio STD-WW

technical data

motor	ECblue	
Efficiency class	IE4	
mains supply	-	1~ 230V 50Hz
ambient temperature, max. limit (t_r)	°C	40
efficiency grade η_{statA}	%	67,8
efficiency grade N_{actual} N_{target}		79,4 62
ErP-conformity		2015 EC controller integrated
grille influence		no

fan data

SFP-class SFP-value (P_{SFP})	- Ws/m^3	3 1221
airflow volume (q_v)	ft^3/min	1316.8
air velocity	ft/s	33.23
pressure, stat. (p_{sF}) tot. (p_F)	in.wg.	2.981 3.221
electrical power input (P_{sys})	W	759
system eff., stat. ($\eta_{sF,sys}$) tot. ($\eta_{F,sys}$)	%	60.8 65.7
fan speed (n) max. (n_{max})	rpm	3584 3600
fan speed, set value ($\%n_{max}$)	%	100
frequency (f_{BP}) (f_{max})	Hz	50 60
voltage (U_{DP})	V	230
current (I_{DP})	A	3.34
acoustics, suction side ($L_{w(A),5}$) ($L_{w,5}$)	dB	75 77
acoustics, pressure side ($L_{w(A),6}$) ($L_{w,6}$)	dB	82 83
dimensions (w x h x d)	in	14.76 x 14.76 x 11.14
product weight (m_{pr})	lb	24.3
k-factor nozzle pres. (k)	-	60
differential pres. nozzle ($p_{sF \text{ nozzle}}$)	Pa	1390

PF:PF_50; Ano:115666; STot:+-10 %






performance curve / acoustics

16/12/2021


version FANselect V 1.01 (211209), AMCA V 1.03 September, 2021 / 1.21.12.09 | 53567 | (user ZAFS43567)

- 1
GR25C-6ID.BD.CR
measured in standard nozzle in installation type A according to ISO 5801
115666/A01 | Portfolio
measurement density 0.072 [lbs/ft³]
STD-WW


air performance p_{sF}



acoustics ($L_{w(A),5}$)



acoustics ($L_{w(A),6}$)



1 GR25C-6ID.BD.CR									
f [Hz]	sum	63	125	250	500	1000	2000	4000	8000
$L_{w(A),5}$	75	41	47	59	69	69	68	67	61
$L_{w,5}$	77	68	63	66	73	70	67	66	62

f [Hz]	sum	63	125	250	500	1000	2000	4000	8000
$L_{w(A),6}$	82	44	51	62	74	78	77	73	68
$L_{w,6}$	83	70	67	69	78	78	76	72	69


FANselect




efficiency grade / power input 16/12/2021
version FANselect V 1.01 (211209), AMCA V 1.03 September, 2021 / 1.21.12.09 | 53567 | (user ZAFS43567)

- 1 **GR25C-6ID.BD.CR** measured in standard nozzle in installation type A according to ISO 5801
115666/A01 | Portfolio measurement density 0.072 [lbs/ft³]
STD-WWW


efficiency grade $\eta_{F,sys}$



efficiency grade $\eta_{SF,sys}$



power input P_{sys}






nominal values

16/12/2021

version FANselect V 1.01 (211209), AMCA V 1.03 September, 2021 / 1.21.12.09 | 53567 | (user ZAFS43567)

1



GR25C-6ID.BD.CR
115666/A01


1~ 200-277V 50Hz P1 0.78kW
4.00-2.90A 3600/MIN 40°C
1~ 200-277V 60Hz P1 0.78kW
4.00-2.90A 3600/MIN 40°C
IP54 THCL155

drawing


16/12/2021

version FANselect V 1.01 (211209), AMCA V 1.03 September, 2021 / 1.21.12.09 | 53567 | (user ZAFS43567)

1



GR25C-6ID.BD.CR
115666/A01




wiring diagram


16/12/2021

version FANselect V 1.01 (211209), AMCA V 1.03 September, 2021 / 1.21.12.09 | 53567 | (user ZAFS43567)

1



GR25C-6ID.BD.CR
115666/A01





system components

16/12/2021

version FANselect V 1.01 (211209), AMCA V 1.03 September, 2021 / 1.21.12.09 | 53567 | (user ZAFS43567)



type	GR25C-6ID.BD.CR
article no.	115666/A01