



RANCO®



Scan for all models, literature and cross reference

1564

1 Year Limited Warranty

TEMPERATURE CONTROLS - COLD CONTROLS



K12L-1529-002

K Series

The Ranco® K Controls are used all over the globe to control the temperature in commercial and domestic refrigeration, air conditioning and heating applications. Typical uses include refrigerators, freezers, bottle and liquid coolers, and refrigerator display cases.

Features and Benefits

- Compact size
- Standard mounting configurations
- Constant/fixed differential
- SPST close-on-rise switching
- Various capillary lengths

Specifications

Part Numbers	Description	Country of Origin	Switch	Cold Cut-In	Cold Cut-Out	Normal Cut-Out	Warm Cut-In	Warm Cut-Out	Constant Cut-In	Capillary Length
K12L-1529-002*	Cold Control International Models	Czech Republic	SPST	NA	-8.3°C	-4.7°C	NA	-0.8°C	5.5°C	2130 mm
K50P-1125-001*	Cold Control International Models	Czech Republic	SPST	-9°C	-18°C	NA	9°C	NA	NA	1200 mm
K50P-1126-001*	Cold Control International Models	Czech Republic	SPST	-18°C	-24°C	NA	-9°C	NA	NA	1200 mm
K50P-1127-001*	Cold Control International Models	Czech Republic	SPST	5°C	2°C	NA	13°C	NA	NA	1200 mm
K50P-6063-001*	Cold Control International Models	Czech Republic	SPST	5°C	-6°C	NA	11°C	NA	NA	1200 mm
K50Q-1125-001*	Cold Control International Models	China	SPST	-9°C	-18°C	NA	9°C	NA	NA	1200 mm
K50Q-1126-001*	Cold Control International Models	China	SPST	-18°C	-24°C	NA	-9°C	NA	NA	1200 mm
K50Q-1127-001*	Cold Control International Models	China	SPST	5°C	2°C	NA	13°C	NA	NA	1200 mm

*International export models