



Solenoid coil, BE230CS

018F6732

Product name: Solenoid coil, Type: BE230CS, Supply voltage [V] AC: 220 - 230, Enclosure rating IP: IP67,
Coil connection: Connection box, Actuator size: 13.5 mm

Contact

+ Add to comparison list

Product details

Documents

Visuals

Product details

Gross weight

0.35 kg

 Net weight

0.31 kg

EAN

5702428519113

Actuator size	13.5 mm
Ambient temperature range [°C] [Max]	50 °C
Ambient temperature range [°C] [Min]	-40 °C
Ambient temperature range [°F] [Max]	120 °F
Ambient temperature range [°F] [Min]	-40 °F
Approval	LLC CDC TYSK
Cable diameter [mm] [Max]	11 mm
Cable diameter [mm] [Min]	6 mm
Coil connection	Connection box
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Conductor area [mm²]	0.75 - 1.5 mm ²
Duty rating	Continuous
Electrical connection	Terminal box
Electrical connection size	Pg 13.5
Enclosure rating IP	IP67
Frequency [Hz]	50/60 Hz



Identical product	018F8732
Packing format	Multi pack
Parts Program name	EV210B EV212B EV220B 15 - 50 EV220B 6 - 22 EV220B 65 - 100 EV222B EV224B EV227B EV250B EV251B
Power consumption 50Hz [VA]	31 VA
Power consumption 60Hz [VA]	24 VA
Power consumption [W] 50Hz	17 W
Power consumption [W] 60Hz	14 W
Product accessories	Solenoid coil accessories
Product group	Solenoid valves
Product name	Solenoid coil
Quantity per packing format	32 pc
Rel. Humidity [% RH] [Max]	100 %
Rel. Humidity [% RH] [Min]	0 %
Serviceable	No
Spare part number	018F6193
Supply voltage 50Hz Max [V]	230 V
Supply voltage 50Hz Min [V]	220 V



Supply voltage 60Hz Max [V]	230 V
Supply voltage 60Hz Min [V]	220 V
Supply voltage [V] a.c. [Max]	230 V
Supply voltage [V] AC [Max]	230 V
Supply voltage [V] AC [Min]	220 V
Type	BE230CS
Type designation	BE230CS

