

CATEGORY / CAT I / A1



**OIL SEPERATOR**

OS 5/8"

**TECHNICAL INFORMATION**

|                                 |                             |
|---------------------------------|-----------------------------|
| Cooler Fluid Type (Refrigerant) | R22,R134a,404A, R407C,R507A |
| Capacity (Volume)               | 2,3 Lt.                     |
| Operating Pressure (PS)         | 33 Bar.                     |
| Test Pressure (PT)              | 48 Bar.                     |
| Allowable Temperature (TS)      | Min.-20°C / Max. 130°C      |
| Packaging Size & Weight         |                             |
| Drawn By                        | Tuncay TEKSEN               |
| Approved                        | Mustafa DEMIRCI             |
| Date                            | 08.04.2013                  |

**CONNECTIONS**

|    |                         | QTY                        |
|----|-------------------------|----------------------------|
| 01 | Inlet Connection        | 5/8" ODS / OS 1 Pcs.       |
| 02 | Outlet Connection       | 5/8" ODS / OS 1 Pcs.       |
| 03 | Oil Return              | 3/8" SAE Flare 1 Pcs.      |
| 04 | Top Cover               | DD11-6222 Steel 3mm 1 Pcs. |
| 05 | Stainless Stel Filter   | 0,22mm Filter 2 Pcs.       |
| 06 | Stainless Seperator     | 1mm 304 1 Pcs.             |
| 07 | Pipe Of Oil Return      | Brass Q8x0,9mm 1 Pcs.      |
| 08 | Float Ball Of Stainless | Q62x1,2mm 1 Pcs.           |
| 09 | On&Off Bracket Of Float | Brass 1 Pcs.               |
| 10 | Needle                  | Stainless 1 Pcs.           |
| 11 | Pin Of Spring Steel     | Spring Stel Q1,9mm 2 Pcs.  |
| 12 | Stainless Latch         | Stainless Stel 304 1 Pcs.  |
| 13 | Bottom Cover            | DD11-6222 Steel 1 Pcs.     |
| 14 | Bolt & Nut              | M8 1 Pcs.                  |
| 15 | Plate Of Mounting       | DD11-6222 Steel 1 Pcs.     |
| 16 | Segman                  | 3 Pcs.                     |
| 17 | Magnet                  | Q13 1 Pcs.                 |
| 18 | Stainless Stick         | Q5 1 Pcs.                  |
| 19 | Pipe & Tube             | Q114 - 3,0 mm 1 Pcs.       |
|    | Colour                  | RAL 5000                   |

Raw Material : 10217-/P235 TR1-EN 10204 3.1 TUBE

**TOLERANS**

| DIN ISO 2768-mK | ISO E |
|-----------------|-------|
| 0,5 - 6 mm      | + 0,1 |
| 6 - 30 mm       | + 0,2 |
| 30 - 120 mm     | + 0,3 |
| 120 - 400 mm    | + 0,5 |
| 400 - 1000 mm   | + 0,8 |

**GVN SOGUTMA**  
 Uniteleri San. ve Tic. Ltd. Şti.  
 www.gvn.com.tr

Tel. : +90 (212) 230 2113 - 232 4147  
 Fak. : +90 (212) 231 6395 - 2255296  
 Add : Döşapdere Cad. Lalezar Sok.  
 No:7, 34375, Pangaltı, İstanbul, TÜRKİYE  
 E-mail : info@gvensogutma.com

BEST QUALITY. BEST SERVICE. BEST PRICE

**MADE IN TURKEY**

