

Electrical flaring tool VET-19Li



| | |
|-----------------------|--|
| Tube | 1/4", 3/8", 1/2", 5/8", 3/4"; optional: 6/8/9/10/12/15/16/18/19mm |
| Flaring shape | JIS B 8607 |
| Operating temperature | 5°C - 40°C |
| Charging time | ~ 30 min |
| Power supply | AC 100-240 V (50-60Hz) |
| Dimensions | 256 x 101 x 100 mm |
| Flaring times | 15 - 20 sek |
| Single charge | 90 flaring (tube 3/8") |
| Speed | 120 rpm |
| Package | case |
| Power | li-battery 7,4 V; 2 Ah |
| Application | soft copper tube |

Electrical flaring tool VET-19Li

| | |
|-----|--|
| Set | flaring tool, battery, charger, case, clamp: 1/4", 3/8", 1/2", 5/8", 3/4" |
|-----|--|

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

Electrical flaring tool VET-19Li

High performance, large capacity lithium battery.

One key operation.

Rechargeable.

No power supply needed.

Quick loading and unloading copper tube.

High quality flares.



Electrical flaring tool VET-19Li

