


Blondelle Pressure Gauge, Ø 60, composite



- Class 1
- 'A Lame Acier' unique bellow mechanism, the highest durability and accuracy
- All combinations of refrigerants possible
- Each gauge calibrated individually
- high quality composite casing
- Admissible overload: 200%
- Possibility to adjust the needle
- Dry or oil filled
- Outlet: vertical or rear
- Fitting: 1/4" SAE or 1/8" NPT

Low Pressure			Reference		Pressure		Refrigerants
Version	Outlet	Fitting	Case	Dial	psi	bar	
Dry	Vertical	1/4" SAE	MA0602V14S				
		1/8" NPT	MA0602V18B				
	Rear	1/4" SAE	MA0602A14S				
		1/8" NPT	MA0602A18B				
Oil filled	Vertical	1/4" SAE	MA1002V14S				
		1/8" NPT	MA1002V18B				
	Rear	1/4" SAE	MA1002A14S				
		1/8" NPT	MA1002A18B				
				1001		-1+10	R507+R404A+R407C Vap. Liq.
				1003		-1+10	R404A+R407C Vap.+R134a
				1005		-1+10	R134a+R407C Vap. Liq.
				1015		-1+30	R744
				1017	-30+290	-1+20	R410A
				1031		-1+20	R407C Vap.Liq.+R410A
				1035		-1+20	R134a+R404A+R410A+R22
				1037		-1+20	R407C+Vap.Liq.+R410A+R22
				1115		-1+10	R134a+R404A+R407C Vap.Liq.
				1123		-1+20	R134a+R404A+R407C+R410A
				5992	-30+140	-1+10	R12+R22+R502
				6060	-30+140	-1+10	R134a
				6070		-1+10	R12+R22+R502
				6125	-30+140	-1+10	R22+R134a
				6171		-1+10	R134a
				6186		-1+10	R22+R134a
				6685		-1+10	R134a+R404A
				6702	-30+140	-1+10	R134a+R404A
				7074		-1+10	R22+R134a+R404A
				7076	-30+140	-1+10	R22+R134a+R404A
				7126	-30+140	-1+10	R290+R600A
				7216		-1+10	R134a+R404A+R507+R407C
				7272		-1+10	R22+R134a+R407C
				7290		-1+10	R23
				7345		-1+10	R134a+R404A+R22+R407C
				7366		-1+10	R407C Vap. Liq.
				7496		-1+10	R507+R407C
				7540		-1+10	R134a+R22+R407C Vap. Liq.
				7552		-1+10	R134a+R22+R404A+R507
				8006		-1+20	R410A



High Pressure			Reference		Pressure		Refrigerants
Version	Outlet	Fitting	Case	Dial	psi	bar	
Dry	Vertical	1/4" SAE 1/8" NPT	MA0602V14S MA0602V18B				
Oil filled	Rear	1/4" SAE 1/8" NPT	MA0602A14S MA0602A18B				
	Vertical	1/4" SAE 1/8" NPT	MA1002V14S MA1002V18B				
	Rear	1/4" SAE 1/8" NPT	MA1002A14S MA1002A18B				
				1002		-1+30	R507+R404A+R407C Vap. Liq.
				1004		-1+30	R404A+R407C Vap.+R134a
				1006		-1+30	R134a+R407C Vap. Liq.
				1018	-30+650	-1+45	R410A
				1029		-1+50	R744
				1032		-1+45	R407C Vap.Liq.+R410A
				1036		-1+45	R134a+R404A+R410A+R22
				1038		-1+45	R407C+Vap.Liq.+R410A+R22
				1116		-1+30	R134a+R404A+R407C Vap.Liq.
				1124		-1+45	R134a+R404A+R407C+R410A
				5993	-30+400	-1+30	R12+R22+R502
				6061	-30+400	-1+30	R134a
				6071		-1+30	R12+R22+R502
				6126	-30+400	-1+30	R22+R134a
				6175		-1+30	R134a
				6188		-1+30	R22+R134a
				6686		-1+30	R134a+R404A
				6703	-30+400	-1+30	R134a+R404A
				7075		-1+30	R22+R134a+R404A
				7077	-30+400	-1+30	R22+R134a+R404A
				7127	-30+400	-1+30	R290+R600A
				7217		-1+30	R134a+R404A+R507+R407C
				7273		-1+30	R22+R134a+R407C
				7291		-1+30	R23
				7346		-1+30	R134a+R404A+R22+R407C
				7367		-1+30	R407C Vap. Liq.
				7497		-1+30	R507+R407C
				7541		-1+30	R134a+R22+R407C Vap. Liq.
				7553		-1+30	R134a+R22+R404A+R507
				8007		-1+45	R410A

			Reference		Pressure		Refrigerants
Version	Outlet	Fitting	Case	Dial	psi	bar	
Oil filled	Vertical	1/4" SAE 1/8" NPT	MA0502V14S MA0502V18B				
	Rear	1/4" SAE 1/8" NPT	MA0502A14S MA0502A18B				
				6355		-1+16	

How to read the tables?

The complete designation of a pressure gauge comprises the reference of the casing, followed by the reference of the dial.

Ex: Pressure gauge diameter 60mm composite, oil filled, rear outlet, 1/4"SAE, -1+10bar / R22+R134a+R407C:

Case: MA1002A14S; Dial: 7272; Reference: MA1002A14S-7272