# **TUBING TOOLS**

## Braze-Rite Adapter

Nitrogen purging adapter for ACR pipe. Quickly connects to manifold gauge hose, and slips



easily and securely into pipe. Allows for bleed of nitrogen through pipe being brazed, keeping the pipes clean and oxide-free. Stepped to fit most common ACR pipe sizes, making it fast to go from one tube to the next. Saves time and money and helps maintain equipment manufacturer's system performance and installation guidelines. No more duct taping your hose to the pipe!

## gas test gauge

To test system pressure for leaks in new installs, use these 3" easy to read test gauges. Fits 3/4" and 1" pipes.



PART NO.	DESCRIPTION
GTBG-12	3-1/2" Test gauge 0-30 lb. 3/4" end
GTBG-16	3-1/2"Test gauge 0-30 lb. 1" end

## Oil Transfer Pump

#### T30251

Designed to pump oil into the system while unit is operating without shutting down for charging. Smoothly pumps oil into the cornpressor on the down stroke while system is under pressure resulting in easier pumping on the positive stroke. The universal tapered rubber adapter is designed to fit all 1, 2-1/2, and 5 gallon containers without additional adapters. Works against 200 psi of pressure and is compatible with all oil types including synethic, mineral, and polyol ester. Pumps 2.6 ounces (78 ml) per stroke.



### Service wrenches

Double end reversible ratchet wrenches feature accurately broached multiple openings and offer the greatest number of uses in a single unit. Choose offset or hex and square ends. Items ending in "U" deonote Made in the USA.



PART NO	DESCRIPTION
T21124	3/16", 1/4" square end and 1/2", 9/16" hex port end
T21127	3/16", 1/4", 5/16", and 3/8"
T21127U	1/2", 3/16" on one end 3/8", 5/16" on other end
T21126U	Offset 1/2", 3/16" on one end 3/8", 5/16" on other end
T21125U	3/8" square end and 1/2" square end

## Gas Pressure Test Kit

This diaphragm gauge scale comes complete in case with hose and hook-up fitting.





PART NO.	DESCRIPTION
29435	Natural and LP gases. Scales 0-20 oz/sq. in; 0-35" of water column
29436	Natural gas only. Scales 0-6 oz/sq. in; 0-10" of water column

## HEX KEY ADAPTER

Heat treated black oxide plated hex key adapter for accessing liquid and suction based valves. Works for 3/16" and 5/16" hex valves.



### Steel Strap

Our Steel Straps are zinc plated and alternate between nail and bolt holes.



PART NO.	DESCRIPTION
PS-10	10' (3 m) steel strap
PS-25	25' (7.6 m) steel strap
PS-50	50' (15 m) steel strap

