

ZP154KCE-TFD

HFC, R-410A, 50Hz, 3- Phase, 380/420 V

Air Conditioning



Production Status: Non U.S. model with restricted sales - Contact your Emerson Climate Technologies Representative.

Performance

<u>Evap(°C)/Cond(°C)</u>	<u>7.2 / 54.4</u>	<u>1.7 / 48.9</u>
<u>RG(°C)/Liq(°C)</u>	<u>18.3 / 46.1</u>	<u>12.8 / 40.6</u>
Capacity (Watts)	37000	33000
Power (Watts):	11600	10200
Current (Amps):	20.80	18.70
EER (COP):	3.22	3.28
Mass Flow (g/s):	236	200
Sound Power (dBA):	76 Avg	81 Max
Vibration (mm(peak- Vibration (mm(peak- Record Date:	0.076 Avg	0.114 Max
	2007-09-12	

Mechanical

Number of Cylinders:	0	Displ(cm ³ /Rev):	142.94
Bore Size(mm):	0.00	Displ(meters ³ /hr):	24.87
Stroke(mm):	0.00		
Overall Length (mm):	263.6	Mounting Length (mm):	190.50
Overall Width (mm):	285.2	Mounting Width (mm):	190.50
Overall Height (mm):	551.6	Mounting Height (mm):	584.9 *
Suction Size (mm):		34 15/16 Stub	
Discharge Size (mm):		22 7/32 Stub	
Oil Recharge (ml):		3135	
Initial Oil Charge (ml):		3253	
Net Weight (kg):		64.86	
Internal Free Volume (cm ³):		14029.84	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	140.0	MCC (Amps):	35.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	27-Sep-1996
LRA Low*:	133.0	Max Operating Current:	31.0		
RLA(=MCC/1.4;use for contactor selection):		25			
RLA(=MCC/1.56;use for breaker & wire size		22.4			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-410A HFC	60	3	460	Air Conditioning