



Function :

- ◆ Compact body design, space saving.
- ◆ Aesthetically pleasing white finish, all-metal housing, advanced fire proof, easy installation and maintenance.
- ◆ Adjustable directional vane that allows you to regulate the direction fo the air flow.
- ◆ Optimized air wheel with large air volume and low noise.
- ◆ Applied rigid fibreglass plastic air wheel, quality aluminum alloy fan wheel is optional for heavy oily smoke environment.
- ◆ Optimized motor operates 5000 hours continuously without any defects.
- ◆ Flexible control methods: switch control, remote control, wire control box, magnetic sensor control
- ◆ Novelty and facile design.
- ◆ Optional functions: UV lamp purification, negative ion generator, dust-proof, electronic dedusting, explosion-proof etc.

Model No.	Specification (mm)	Rated Voltage (V)	Rated Frequency (Hz)	Installation Height (m)	Input Power (W)	Input Power (kW)	Air Speed (m/s)	Air Volume (m ³ /h)	Noise (dB)	Dimension (mm)	Net Weight (kg)
FM3009	900	220-240	50	2.3-3.0	100/95	0.60	11	1520	54	900×200×165	8.5
FM3009Y	900	220-240	50	2.3-3.0	100/95	0.60	11	1520	54	900×200×165	8.5
FM3010	1000	220-240	50	2.3-3.0	130/110	0.65	11	1685	55	1000×200×165	9.0
FM3010Y	1000	220-240	50	2.3-3.0	130/110	0.65	11	1685	55	1000×200×165	9.0
FM3012	1200	220-240	50	2.3-3.0	135/130	0.75	11	2000	56	1200×200×165	10.0
FM3012Y	1200	220-240	50	2.3-3.0	135/130	0.75	11	2000	56	1200×200×165	10.0
FM3015	1500	220-240	50	2.3-3.0	170/155	1.00	11	2500	59	1500×200×165	13.0
FM3015Y	1500	220-240	50	2.3-3.0	170/155	1.00	11	2500	59	1500×200×165	13.0