Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

SECTION 1. IDENTIFICATION

Product name : Honeywell Refrigerant 134a

Number : 00000023721

Product Use Description : Refrigerant, Propellant

Manufacturer or supplier's

details

Honeywell International Inc. 115 Tabor Road

Morris Plains, NJ 07950-2546

For more information call : 800-522-8001

+1-973-455-6300(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

:

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Color : colourless

Odor : weak

Classification of the substance or mixture

Classification of the : Gases under pressure, Liquefied gas

substance or mixture Simple Asphyxiant

GHS Label elements, including precautionary statements

Page 1 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

Symbol(s)

Signal word : Warning

Hazard statements : Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary statements : Storage:

Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise

classified

: May cause cardiac arrhythmia.

May cause frostbite.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Substance

Chemical name	CAS-No.	Concentration
1,1,1,2-Tetrafluoroethane	811-97-2	99.80 %

SECTION 4. FIRST AID MEASURES

General advice : First aider needs to protect himself. Move out of dangerous

area.

Inhalation : Move to fresh air. If breathing is irregular or stopped,

administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do

not give drugs from adrenaline-ephedrine group.

Page 2 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

Skin contact : After contact with skin, wash immediately with plenty of water.

If there is evidence of frostbite, bathe (do not rub) with

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a

physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Notes to physician

Indication of immediate medical attention and special treatment needed, if

necessary

Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-

bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : The product is not flammable.

Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific hazards during

firefighting

: Contents under pressure.

This product is not flammable at ambient temperatures and

atmospheric pressure.

However, this material can ignite when mixed with air under

pressure and exposed to strong ignition sources.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

Page 3 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

Fire may cause evolution of: Halogenated compounds Hydrogen fluoride Carbon oxides

Carbonyl halides

Special protective equipment

for firefighters

: In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.

No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Wear personal protective equipment. Unprotected persons

must be kept away.

Remove all sources of ignition.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

After release, disperses into the air.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

Avoid accumulation of vapours in low areas.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is >= 19.5%.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

The product evapourates readily.

Methods and materials for containment and cleaning

up

Ventilate the area.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe

handling

Handle with care.

Avoid inhalation of vapour or mist.

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment.

Page 4 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

Use only in well-ventilated areas.

Pressurized container. Protect from sunlight and do not expose

to temperatures exceeding 50 °C.

Follow all standard safety precautions for handling and use of

compressed gas cylinders. Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.

Always replace cap after use.

Advice on protection against fire and explosion

The product is not flammable.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Storage

Conditions for safe storage,

including any incompatibilities

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even

after use.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.

Perform filling operations only at stations with exhaust

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields

Page 5 / 13

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection Leather gloves

In case of contact through splashing:

Protective gloves Neoprene gloves

Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection Avoid skin contact with leaking liquid (danger of frostbite).

Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Wear a positive-pressure supplied-air respirator.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

Exposure Guidelines					
Components	CAS-No.	Value	Control	Upda	Basis
			parameters	te	
1,1,1,2- Tetrafluoroethane	811-97-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1,2- Tetrafluoroethane	811-97-2	TWA : Time	4,240 mg/m3 (1.000 ppm)	2007	WEEL:US. OARS. WEELs Workplace

1,1,1,2-	811-97-2	TWA:	4,240 mg/m3	2007	WEEL:US. OARS.
Tetrafluoroethane		Time	(1,000 ppm)		WEELs Workplace
		weighted			Environmental
		average			Exposure Level
					Guide, as amended

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

1,1,1,2- Tetrafluoroethane	TWA: 4,240 mg/m3 Time (1,000 ppm) weighted average	2007 WEEL:US. OARS. WEELs Workplace Environmental Exposure Level Guide, as amended
-------------------------------	---	--

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas

Color : colourless

Odor : weak

pH : Note: neutral

Melting point/range : -101 °C

Boiling point/boiling range : -26.2 °C

Flash point : Note: Not applicable

Evaporation rate : > 1

Method: Compared to CCl4.

Lower explosion limit : Note: None

Upper explosion limit : Note: None

Vapor pressure : 5,915 hPa

at 21.1 °C(70.0 °F)

14,713 hPa

at 54.4 °C(129.9 °F)

Vapor density : 3.5

Page 7 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

Density : 1.2 g/cm3

Water solubility : 1.5 g/l

Partition coefficient: n-

octanol/water

: log Pow: 1.06

Note: The product is more soluble in octanol.

Ignition temperature : > 750 °C

Auto-ignition temperature : > 750 °C

Decomposition temperature : > 250 °C

Viscosity, dynamic : Note: no data available

Viscosity, kinematic : Note: no data available

Molecular weight : 102.02 g/mol

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Conditions to avoid : Pressurized container. Protect from sunlight and do not

expose to temperatures exceeding 50 °C. Decomposes under high temperature.

Some risk may be expected of corrosive and toxic

decomposition products.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials : Oxidizing agents

Page 8 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

Finely divided metal powders such as aluminum, magnesium,

or zinc.

Hazardous decomposition

products

: Halogenated compounds

Hydrogen fluoride Carbonyl halides Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: > 500000 ppm

Exposure time: 4 h Species: Rat

Sensitisation : Cardiac sensitization

Species: dogs

Note: No-observed-effect level 50 000 ppm Lowest observed

effect level 75 000 ppm

Repeated dose toxicity : Species: Rat

NOEL: 40000 ppm

Genotoxicity in vitro : Test Method: Ames test

Result: negative

Method: OECD Test Guideline 471

Genotoxicity in vivo : Species: Mouse

Result: negative

Reproductive toxicity : Species: Mouse

Application Route: Inhalation

NOEL: 50,000 ppm

Teratogenicity : Species: RabbitApplication Route: Inhalation

Page 9 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

NOEL: 40,000 ppm

Method: OECD Test Guideline 414

Further information : Note: Vapours are heavier than air and can cause suffocation

by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. Avoid skin contact with

leaking liquid (danger of frostbite).

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to bacteria : Growth inhibition

EC10: > 730 mg/l Exposure time: 6 h

Species: Pseudomonas putida

Elimination information (persistence and degradability)

Biodegradability : Result: Not rapidly biodegradable

Value: 3 %

Method: OECD 301 D

Further information on ecology

Ecotoxicology Assessment

Results of PBT assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT)., This substance

is not considered to be very persistent and very bioaccumulating (vPvB).

Additional ecological

information

: Accumulation in aquatic organisms is unlikely.

This product contains greenhouse gases which may

contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any

residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

Page 10 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

regulations.

Note : This product is subject to U.S. Environmental Protection

Agency Clean Air Act Regulations Section 608 in 40 CFR Part

82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3159

Proper shipping name : 1,1,1,2-Tetrafluoroethane

Class 2.2

Packing group

Hazard Labels 2.2

IATA UN/ID No. : UN 3159

Description of the goods : 1,1,1,2-Tetrafluoroethane

Class : 2.2 Hazard Labels : 2.2 Packing instruction (cargo : 200

aircraft)

Packing instruction : 200

(passenger aircraft)

IMDG UN/ID No. : UN 3159

Description of the goods : 1,1,1,2-Tetrafluoroethane

Class : 2.2
Hazard Labels : 2.2
EmS Number : F-C, S-V
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances : On TSCA Inventory

Control Act

Australia. Industrial : On the inventory, or in o

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Page 11 / 13

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Existing Chemicals

Inventory (KECI)

: On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing

Chemical Substances

(IECSC)

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

. Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Acute Health Hazard

Sudden Release of Pressure Hazard

Honeywell

Honeywell Refrigerant 134a

10657321

Version 1.0 Revision Date 11/08/2019 Print Date 02/08/2024

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

SECTION 16. OTHER INFORMATION

HMIS III NFPA
Health hazard : 1 2
Flammability : 1 1
Physical Hazard : 0
Instability : 0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group