

BLR/RV Rotolock Valve

- The Max operating Pressure of the valve body pressure 4.8 MPa
- Use Medium temperature -40 °C to 150°C
- Use R22 R134a R404A and other refrigerant

Model	Body (mm)	Connections			PIC
		Service Connection	Rotolock Connection	Inlet Connection	
BLR/RV-202	20	2 pcs. x 1/4" SAE	3/4"	1/4" ODS	
BLR/RV-2010	20	2 pcs. x 1/4" SAE	1"	3/8" ODS	
BLR/RV-2012	20	2 pcs. x 1/4" SAE	1"	1/2" ODS	
BLR/RV-2013	20	2 pcs. x 1/4" SAE	1"	5/8" ODS	
BLR/RV-222	22	2 pcs. x 1/4" SAE	1 1/4"	1/2" ODS	
BLR/RV-223	22	2 pcs. x 1/4" SAE	1 1/4"	5/8" ODS	
BLR/RV-225	22	2 pcs. x 1/4" SAE	1 1/4"	3/4" ODS	
BLR/RV-302	30	2 pcs. x 1/4" SAE	1 1/4"	3/4" ODS	
BLR/RV-303	30	2 pcs. x 1/4" SAE	1 1/4"	7/8" ODS	
BLR/RV-308	30	2 pcs. x 1/4" SAE	1 3/4"	7/8" ODS	
BLR/RV-310	35	2 pcs. x 1/4" SAE	1 3/4"	1 1/8" ODS	
BLR/RV-353	35	2 pcs. x 1/4" SAE	1 3/4"	1 3/8" ODS	
BLR/RV-355	35	2 pcs. x 1/4" SAE	1 3/4"	1 5/8" ODS	
BLR-RV-501	50	2 pcs. x 1/4" SAE	2 1/4"	1-3/8"ODS	
BLR/RV-503	50	2 pcs. x 1/4" SAE	2 1/4"	1 5/8" ODS	
BLR/RV-504	50	2 pcs. x 1/4" SAE	2 1/4"	2 1/8" ODS	